



3 a transmission unit

4 for transmitting the file containing the slide data to  
5 the display device,

6 wherein the data obtaining unit obtains the file by receiving  
7 the file transmitted by the transmission unit.

1 3. The presentation system of Claim 2,

2 wherein the terminal further includes  
3 an editing unit

4 for editing the slide data in accordance with an input  
5 from outside.

1 4. The presentation system of Claim 1,

2 wherein the part which is made invisible by the data modifying  
3 unit is a part of text put in the first slide image by utilizing functions  
4 of presentation software.

1 5. The presentation system of Claim 1,

2 wherein the part which is made invisible by the data modifying  
3 unit is a part of text put in a textbox which is embedded in the first  
4 slide image.

1 6. The presentation system of Claim 1,

2 wherein the display device further includes  
3 a modification condition setting unit

0055049-00270  
FD-250 (Rev. 6-10-59)

4 for receiving settings regarding (a) a method of  
5 modification to be executed by the data modifying unit,  
6 and/or (b) conditions to be satisfied by parts of data  
7 to be modified.

1 7. A presentation system comprising a display device and a terminal,  
2 the display device includes

3 a data obtaining unit

4 for obtaining the file containing slide data which  
5 indicates the first slide image, the first slide image  
6 including one or more invisible parts;

7 a first display unit;

8 a first display image setting unit

9 for making the first display unit display the first slide  
10 image, based on the slide data;

11 a data modifying unit

12 for modifying the slide data to make the invisible parts  
13 of the first slide image visible;

14 an image expansion unit

15 for generating image data of the second slide image from  
16 slide data modified by the data modifying unit;

17 an image data compression unit

18 for compressing the image data of the second slide image;

19 and

20 a transmission unit

TO: "64059660"

21                   for transmitting the image data compressed by the image  
22                   data compression unit to the terminal; and  
23 the terminal includes  
24                   a reception unit  
25                   for receiving the image data transmitted by the  
26                   transmission unit;  
27                   an image data decompression unit  
28                   for decompressing the image data received by the reception  
29                   unit;  
30                   a second display unit; and  
31                   a second display image setting unit  
32                   for making the second display unit display the second slide  
33                   image, based on the decompressed image data.

1   8. The presentation system of Claim 7,  
2                   wherein the display device further includes  
3                   a modification condition setting unit  
4                   for receiving settings regarding (a) a method of  
5                   modification to be executed by the data modifying unit,  
6                   and/or (b) conditions to be satisfied by parts of data  
7                   to be modified.

1   9. A display device comprising:  
2                   a data obtaining unit  
3                   for obtaining a file containing a first slide data which

FD-260 (Rev. 6-15-55)

4           indicates a first slide image;

5           a data modifying unit

6           for executing at least one of the following processes.

7           (a) Creates the second slide data which indicates the

8           second slide image by modifying the first slide data, the

9           second slide image being an image which has one or more

10          parts of the first slide image invisible, (b) creates a

11          second slide data which indicates a second slide image

12          by modifying the first slide data, the second slide image

13          being an image of one or more invisible parts of the first

14          image modified to be visible;

15          a display unit; and

16          a display image setting unit

17          for making the display unit display a slide image based

18          on the first slide data or the second slide data, wherein

19          the displayed image is (a) the second slide image if the

20          second slide image is a slide image which has one or more

21          parts of the first slide image part invisible, and (b)

22          the first slide image if the second slide image is an image

23          of one or more invisible parts modified to be visible.

1   10. The display device of Claim 9, wherein the data obtaining unit

2   includes

3          a reception unit

4          for receiving the file.

FD-350 (Rev. 5-22-64)

1 11. The display device of Claim 9 further comprising:

2 an image expansion unit

3 for generating image data of a first slide image or a second  
4 slide image from a first slide data or a second slide data,  
5 wherein the slide image for which the image data is  
6 generated is the first slide image if the second slide  
7 image is an image of one or more parts of the first slide  
8 image made invisible, and is the second slide image if  
9 the second image is an image of one or more invisible parts  
10 of the first image modified to be visible;

11 an image data compression unit

12 for compressing the image data which is generated by the  
13 image expansion unit; and

14 a transmission unit

15 for transmitting the compressed image data.

1 12. The display device of Claim 9,

2 wherein the part which is made invisible or visible by the data  
3 modifying unit is a part of text put in a slide image by utilizing  
4 functions of presentation software.

1 13. The display device of Claim 9,

2 wherein the part which is made invisible or visible by the data  
3 modifying unit is a part of text put in a textbox which is embedded

4 in the slide image.

1 14. The display device of Claim 9,

2 wherein the data modifying unit includes

3 a deletion unit

4 for deleting a part which corresponds to an invisible part

5 in the second slide image from the first slide data.

1 15. The display device of Claim 9,

2 wherein the data modifying unit includes

3 a color modifying unit

4 for modifying the color setting of a part which corresponds

5 to an invisible or a visible part in the second slide image

6 in contrast to the first slide data.

1 16. The display device of Claim 9,

2 wherein the data modifying unit includes

3 a background color modification unit

4 for modifying the background color setting in contrast

5 to the first slide data.

1 17. The display device of Claim 9 includes

2 a modification condition setting unit

3 for receiving settings regarding (a) a method of

4 modification to be executed by the data modifying unit,

0995049-09270  
T02260-04099660

5 and/or (b) conditions to be satisfied by parts for a  
6 modification of the parts to take place.

1 18. The display device of Claim 9,

2 wherein the display control unit includes

3 a switching unit

4 for switching whether to make the display unit display  
5 the first or the second slide image.

1 19. A program which is operable by a processor provided in a display  
2 device includes

3 a file obtaining step

4 for obtaining a file including a first slide data which  
5 indicates a first slide image;

6 a data modifying step

7 for executing at least one of the following processes.

8 (a) Creates a second slide data which indicates the second  
9 slide image by modifying the first slide data, wherein  
10 the second slide image is an image which has one or more  
11 parts of the first slide image invisible (b) creates a  
12 second slide data which indicates a second slide image  
13 by modifying the first slide data, wherein the second image  
14 is an image of the first slide image which has the invisible  
15 parts modified to be visible.



